



0799

Vison Byggprodukter AB, Poppelg. 4, 234 35 Lomma

14

0799-CPR-7720101

**EN 13859-1:2010 - Flexible sheets for waterproofing**

**BISON DIFFTAK 175** (Ref nr: 005-0511021-X00-C0711)

<b>Weight (EN 1849-2)</b>	175 g/m <sup>2</sup> (+/-10 %)
<b>Reaction to fire (EN 13501-1)</b>	E
<b>Water tightness (EN 1928/EN 13859-1)</b>	W1
<b>Tensile Strength (EN 12 311-2)</b>	MD: 270 N (+/-20 %) CD: 220 N (+/-20 %)
<b>Tensile Elongation (EN 12311-2)</b>	MD: 50% (+/-20 %) CD: 40% (+/-20 %)
<b>Tear strength (EN 12310-1)</b>	MD: 150 N (+/-20 %) CD: 160 N (+/-20 %)
<b>Water vapour transmission (EN ISO 12572)</b>	sd-value: 0,04 m (+/- 20 %)
<b>Flexibility at low temperature (EN 1109)</b>	-20° C
<b>Water tightness after Artificial ageing (EN 1928)</b>	Pass
<b>Tensile Strength after Artificial ageing (EN 12311-1)</b>	Pass
<b>Dangerous substances</b>	contains no dangerous subst.

*NPD = No Performance Determined. MD: = Machine Direction, CD: = Cross direction.*